

TW X-98






TW X-98

Tyre change

Semi-Autom side swing arm design





Semi-automatic Swing-arm design | Item No.: TW X-98

Description

Our multi-talent for all standard, low profile and run flat tyres. Two help-arms for more efficiency.

Features

- 1A Quality built with CE-Certificate
- Manufactured in accordance to ISO 9001
- Mounting head can be moved to the side
- Solid construction
- Pneumatic mounting head adjustment
- Powerful bead breaker (2500 kg)
- Self centering 4-jaw clamping system · Large clamping range for cars and vans
- (Outside 12"- Inside 28") Integrated air booster in the clamping jaws
- Exchangeable plastic protectors for the
- High quality stainless steel components in the inner part
- Precise control block with STOP function.
- Powerful electrical motor
- · Clamping jaws made of special steel

Delivery contents

- Tyre changer with maintenance unit
- · Air filler and lifting lever
- Bead press and edge protection • Plastic protectors for the clamping jaws (4 pcs.)
- · Plastic protectors for the mounting head



Details






(on page 42) before you buy your Tyre fitting machine



(1) Two help-arms for more efficiency (2) Powerful air jets in all clamping jaws (3) Large clamping range (4) Powerful bead breaker

Dimensions | Technical data | Accessories





Extensive accessories

*Please note: The products are being sold as the 400-volt model, if desired, please specify the 230-volt version

Technical Data: TW X-98	
Clamping range outside	12" - 26"
Clamping range inside	14" - 28"
Wheel diameter (max.)	45" (1143 mm)
Wheel width (max.)	16" (406 mm)
Bead breaker force	2500 kg
Air supply	8 - 10 bar
Power supply	400 V or 230 V*
Motor power	0,75 / 1,1 kW
Noise level	<70 dB
Weight (approx.)	276 kg

Contact us personally: Monday-Friday from 9 am - 6 pm

35