

# LOW PROFILE HYDRAULIC JACK



- 1300 082 002
  - sales@proworkshopgear.com.au
- www.proworkshopgear.com.au
- 3/21 Groves Ave, Mulgrave NSW 2756 Sydney Australia



#### www.jackarooz.com.au

#### J-ELPSJ15T Jackaroo 1.5 Ton Extra Low-Profile Servive Jack



- Extra Low-Profile Service Jack, high lift 610 MM Perfect for cars with Low chassis
- Heavy-duty construction frame provides stability and durability
- Built-in safety valve protects against jack over-loading that means safe work and longer operation life
- Swivel saddle and rear casters provide easy maneuvering and positioning
- Hydraulic oil by-pass system protect ram from being over-extended

Model	Capacity	Product Size	N.W.	G.W.	Minimum Height	Maximum Hieght
J-ELPSJ15T	1500KG	915*385*160MM	44.5KG	46.5 KG	70MM	610MM

# HYDRAULIC JACK▼



- 1300 082 002
  - sales@proworkshopgear.com.au
- www.proworkshopgear.com.au
  3/21 Groves Ave, Mulgrave NSW 2756 Sydney Australia



#### J-LPSJ35T Jackaroo 3.5 Ton Low Profile Service Jack



## J-QLSJ28T Jackaroo 2.8 Ton Quick Lift Service Jack



- Heavy-duty construction frame provides stability and durability
- Built-in safety valve protects against jack over-loading that means safe work and longer operation life
- Swivel saddle and rear casters provide easy maneuvering and positioning
- Hydraulic oil by-pass system protect ram from being over-extended
- "Quick Start" double pump technology for fast operation that means save more time during operation

Model	Capacity	Product Size	N.W.	G.W.	Minimum Height	Maximum Hieght
J-LPSJ35T	3500KG	790*355*180MM	44KG	46KG	95MM	552MM
J-QLSJ28T	2800KG	682*344*155MM	30.7KG	33KG	133MM	465MM

# JACK/JACK STAND



1300 082 002

 $\times$ 

- sales@proworkshopgear.com.au
- www.proworkshopgear.com.au
  3/21 Groves Ave, Mulgrave NSW 2756 Sydney Australia



www.jackarooz.com.au

## J-PSJS22T Jackaroo 22 Ton Pin Style Jack Stands

Feat	ures				
· )	Heavy Du Rigidity Sold and			-	
Model		Capacity	Product Size	N.W.	G.W.
J-PSJS	22T	22TON	250*250MM	27.5KG	28.8KG

## J-AHJ22T Jackaroo 22 Ton Air Hydraulic Jack



- High Quality Professional Grade
- Heavy Duty "T" Handle with Three Locking Positions; 90°, 45°, 0°
- Chrome Plated Rams to Resist Rust and Wear
- Built-In By-Pass Device to Protect Hydraulic System from Over Pumping Damage
- Built-In Inline Air Filter to Extended Motor Life
- High Speed Turbo Motor for Efficient Effortless Operation
- High quality lead-free paint ensures long-lasting wear and prevents rust
  - Temperature-resistant hydraulic oil
    - Durable hydraulic pump

Model	Capacity	Product Size	N.W.	G.W.	Minimum Height	Maximum Hieght	Extension Screw	Base Size
J-AHJ22T	22000KG	520*330MM	43KG	48 KG	228MM	457MM	107MM	520*330MM

# **JACK**



1300 082 002 C

 $\times$ 

- sales@proworkshopgear.com.au www.proworkshopgear.com.au
- 0 3/21 Groves Ave, Mulgrave NSW 2756 Sydney Australia



www.jackarooz.com.au

### SAHJ60-3JC Jackaroo Air Hydraulic Jack 3 stage (60T/30T/12T)



### **Features**

- Integrated operation valve that means time efficient and safe lowering
- Minimum height Only 160 mm minimum height, suitable for the maintenance and repair of buses and trucks with low chassis
- General purpose low jack for mid rigid truck & amp; bus applications.
- Dual operation valve for lifting and lowering
- Easy access oil level check point
  - Hard chrome coated piston rod for longer operation life

#### SAHJ80-3JC Jackaroo low profile Air Hydraulic Jack 3 stage



- Integrated operation valve that means time efficient and safe lowering Minimum height Only 175 mm minimum height, suitable for the maintenance and repair of heavy
- trucks and plant equipment with low chassis
- General purpose jack for heavy trucks & amp; plant equipment
- Dual operation valve for lifting and lowering
- Easy access oil level check point
- Hard chrome coated piston rod for longer operation life

Model	Maximum Load	Work Pres- sure	Minimum Height	Maximum Height	Lifting Heights	Extension	Net weight
SAHJ60-3JC	60T/30T/12T	0.8-1.2 MPA	160MM	472MM	60T: 62MM 30T: 61MM 12T: 69MM	75+45 MM	61KG
SAHJ80-3JC	80T/50T/25T	0.8-1.2MPA	175MM	542MM	80T: 82MM 50T: 81MM 25T: 84mm	75+45MM	73KG





1300 082 002

sales@proworkshopgear.com.au

 www.proworkshopgear.com.au
 3/21 Groves Ave, Mulgrave NSW 2756 Sydney Australia



www.jackarooz.com.au

## SAHJ80-2DC Jackaroo Air Hydraulic Jack 2 stage (80T/40T)



#### **Features**

- Air Hydraulic Jack 2, suitable for heavy trucks & plant equipment
- Integrated operation valve that means time efficient and safe lowering
- General purpose jack for heavy trucks & amp; plant equipment
- Dual operation valve for lifting and lowering
- Easy access oil level check point
- Hard chrome coated piston rod for longer operation life

#### SAHJ80-2DSC Jackaroo Air Hydraulic Jack 2 stage (80T/40T) with telescopic handle



- Air Hydraulic Jack suitable for heavy trucks & plant equipment
- Integrated operation valve that means time efficient and safe lowering
- Telescopic handle to increase maneuver in tight places
- General purpose jack for heavy trucks & amp; plant equipment
- Dual operation valve for lifting and lowering
- Easy access oil level check point
- Hard chrome coated piston rod for longer operation life

Model	Maximum Load	Work Pres- sure	Minimum Height	Maximum Height	Lifting Heights	Extension	Net weight
SAHJ80-2DC SAHJ80-2DSC	80T/40T	0.8-1.2MPA	190MM	492MM	80T: 100MM 40T: 82MM	75+45MM	57KG

# JACK STAND



- 1300 082 002
  - sales@proworkshopgear.com.au
- www.proworkshopgear.com.au
  3/21 Groves Ave, Mulgrave NSW 2756 Sydney Australia



www.jackarooz.com.au

#### J-SPLRJS3T/ J-SPLRJS6T Jackaroo Safe Pin Lock Rachet Jack Stands



### **Features**

- Solid casted ratchet bar provides strength and multiple positions for easy height adjustment
  - Safety counter-weighted pawl ensures ratchet bar is engaged in position
  - Heavy duty stamped steel construction provides stability and rigidity Sold and to be used only in pairs
    - Safety Pin double locking ratchet action.

#### J-QALRJS4T/J-QALRJS6 Jackaroo Quick Auto Lift Rachet Jack Stands



- Solid casted ratchet bar provides strength and multiple positions for easy height adjustment
- Safety counter-weighted pawl ensures ratchet bar is engaged in position
- Heavy duty stamped steel construction provides stability and rigidity Sold and to be used only in pairs
  - Patented quick lifting design will lift the ratchet bar to the desired height with the simple raise of the locking handle

Model	Capacity	Product Size	N.W.	G.W.	Minimum Height	Maximum Height
J-SPLRJS3T	3TON	207*188MM	7KG	7.5KG	300MM	444MM
J-SPLRJS6T	6TON	285*250MM	14KG	14.6KG	400MM	620MM
J-QALRJS4T	4TON	220*188MM	10.4KG	11.5KG	340MM	510MM
J-QALRJS6T	6TON	280*248MM	14.4KG	15.2KG	400MM	620MM

# TRUCK WHEEL DOLLY



- 1300 082 002
- sales@proworkshopgear.com.auwww.proworkshopgear.com.au
- 3/21 Groves Ave, Mulgrave NSW
  2756 Sydney Australia



# J-TWD680K Jackaroo 680 Kg Truck Wheel Dolly



- Hydraulic system provides easy lifting to remove and install single and duplex tires as well as complete wheel hub assembly
- Heavy duty tubular construction with adjustable cradle rollers and desired lifting height

Model	Capacity	Product Size	N.W.	G.W.
J-TWD680K	1500LBS	1800*1090*895MM	70KG	74KG

# Engine Crane▼



- 1300 082 002
  - sales@proworkshopgear.com.au
- www.proworkshopgear.com.au
- 3/21 Groves Ave, Mulgrave NSW 2756 Sydney Australia



## J-EC2T Jackaroo 2 TON 4 Stage Engine Crane



- Self-acting mechanical lock can be engaged in 3 positions
- Heavy duty steel constructions provide stability and rigidity
- Non-slip foot pedal provides easy lifting operation
- Swivel castors allow smooth maneuvering and positioning
  Rubber padded lifting platform protects object from scratching

Model	Capacity	Product Size	N.W.	G.W.	Lifting Rate
J-EC2T	2000KG	1745*850*1460MM	86KG	92KG	(240MM) 1840MM

# UNDER HOIST



- 1300 082 002
  - sales@proworkshopgear.com.au
- www.proworkshopgear.com.au
  3/21 Groves Ave, Mulgrave NSW 2756 Sydney Australia



# J-UHAS Jackaroo 680 Kg Under Hoist Auxiliary Stand



- Heavy Duty Stamped/Formed Steel Construction Provides Stability and Rigidity.
- Designed to Support Vehicle Components, Not the Vehicle. Ideal to Support Any Task Which Requires Relieving Pressure Off of the Vehicle Components.
- Height Adjustment Spin Handle that Provides Easy Adjustment to Work Height.
- Foot Pedal Allows for Easy Load Movement.

Model	Capacity	N.W.	G.W.	Minimum Height	Maximum Height
J-UHAS	680KG	15.3KG	17KG	1360MM	2032MM

# **MOTORBIKE STAND▼**



- 1300 082 002 ¢
- sales@proworkshopgear.com.au www.proworkshopgear.com.au
- 0 3/21 Groves Ave, Mulgrave NSW 2756 Sydney Australia



## J-MMS680K Jackaroo 680 Kg Motorbike Mobile Stand

 $\succ$ 



- Self-acting mechanical lock can be engaged in 3 positions
- Heavy duty steel constructions provide stability and rigidity
- Non-slip foot pedal provides easy lifting operation
- Swivel castors allow smooth maneuvering and positioning Rubber padded lifting platform protects object from scratching

Model	Capacity	Product Size	N.W.	G.W.	Minimum Height	Maximum Height
J-MMS680K	680KG	790*370*330MM	26.8KG	28.5KG	118MM	368MM



#### About us:

With over 30-year experience in the auto-mechanical industry, we have developed a wealth of knowledge and experience, combined with our passion for tools and Equipment to bring you PRO WORKSHOP GEAR. No corners can be cut with our Quality + Reliability + Affordability core values and

every intention of safety first!

Many of you may remember me through my previous business, Top Tech Tools,

Blacktown Tool man, or further back in my truck mechanic business in Sydney and WA Perth, if so don't hesitate to reconnect and receive our quality support in your business.

We also welcome new technicians to reach out for advice. We will give you excellent guidance and support in the early years of your careers that you will use for the rest of your careers.

Oh, almost forgot, "Jackaroo" is our registered brand, so where you see that jumping kangaroo and jack, that's us!

-Ryan, CEO & Founder

- **L** 1300 082 002
- 🔀 sales@proworkshopgear.com.au
- www.proworkshopgear.com.au
- 3/21 Groves Ave, Mulgrave NSW 0 2756 Sydney Australia